

General Protocol Microbiological Incubator, 75L, 120Vac 60Hz



Features:

- Gravity convection provides gentle air flow and minimal drying out
- Temperature range from ambient +5° to 75°C
- Temperature uniformity of $\pm 0.6^{\circ}\text{C}$ (measured at 37°C)
- Temperature stability of $\pm 0.2^{\circ}\text{C}$ (measured at 37 °C)
- Corrosion-resistant stainless-steel chamber (AISI 430)
- Intuitive user interface for setting temperature
- Large, easy to read vacuum fluorescent display
- Internal glass door allows sample viewing without impacting temperature
- Exceptionally small footprint

Specifications:

Convection Technology	Gravity Convection
Controller	Microprocessor control with vacuum fluorescent display
Temperature Range	ambient +5°C to 75°C
Temperature Uniformity at 37°C	$\pm 0.6^{\circ}\text{C}$
Temperature Stability at 37°C	$\pm 0.2^{\circ}\text{C}$
Footprint	0.3sq. m (3.2sq. ft.)
Max. Shelf Load	25kg (55 lbs.)
Weight	40kg (88lbs.)
Chamber volume	75L (2.6cu.ft.)
Interior D x W x H	16.3" x 13.9" x 20.0" / 41.4 x 35.4 x 50.8 cm
Exterior L x W x H	22.2" x 20.9" x 28.3" / 56.5 x 53 x 72 cm
Shelves (Supplied/Max)	2 / 13
Power	120V, 60Hz, 300W, 2.5A
Plug type	Nema 5-15 US
Certifications/Compliance	cCSAus

