

## PH920/PH930 Precision Ph



## SPECIFICATIONS

Model	PH920
pH Range	-2.000~20.000pH
pH Accuracy	±0.002pH
Resolution	0.001, 0.01, 0.1pH, selectable
mV Range	-1999.9~1999.9mV
mV Accuracy	±0.2mV
Resolution	0.1, 1mV, selectable
Calibration Points	Up to 5 points
Calibration Solutions	USA(pH1.68/4.01/7.00/10.01/12.45), NIST(pH1.68/4.01/6.86/9.18/12.45), DIN(pH1.09/4.65/6.79/9.23/12.75)
Temperature Range	0~105°C, 32~221°F
Temperature Accuracy	±0.5°C, ±0.9°F
Temperature Calibration	Manual
Temperature Compensation	0~100°C, 32~212°F, Automatic or Manual
Auto-Off	Manual or Automatic (10, 20, 30 minutes after last key pressed, selectable)
Hold Function	Manual or Automatic
Stability Conditions	Low or High, selectable
Calibration due reminder	0 to 30 days
Reset Function	Yes
Memory	500 data sets with Date/Time stamping
Output	USB Communication Interface
Connector	BNC
LCD Display	Custom dual-display LCD (130×110mm)
Power Requirements	DC5V, using AC adapters, 220VAC/50Hz
Dimensions	210(L)×188(W)×60(H)mm
Weight	1.2kg

