

BIOBASE SK-L180-Pro



SK-O330-Pro/
SK-L330-Pro
with universal
attachment

SK-O180-Pro/
SK-L180-Pro
with flask fixing clip
and attachment

SK-D3309-Pro
LCD Digital 3D Shaker,
90Attachment with
non-slip mat

SK-R330-Pro LCD Digital
Rocking Shaker
Attachment with
non-slip mat

SPECIFICATIONS

Model	SK-O330-Pro SK-L330-Pro	SK-O180-Pro SK-L180-Pro
Power supply	110/220V, 50/60Hz	
Consumption	30W	
Shaking movement	Orbital /Linear	
Orbital diameter [mm]	10	4
Max. shaking weight (with attachment) [kg]	7.5	2.5
Motor type	External rotor brushless motor	
Motor rating input [W]	28	
Motor rating output [W]	15	
Speed range [rpm]	100-500 (Orbital)	100-800 (Orbital)
	100-350 (Linear)	100-350 (Linear)
Speed display	LCD	
Timer	Yes	
Timer display	LCD	
Time setting range [min]	1-1199	
Run type	Timing / Continuous operation	
Size [W*H*D mm]	420*370*100	340*300*100
Weight [kg]	13.5	8.1
Permissible ambient temp.	5-40°C	
Permissible relative humidity	80%	
Protection class acc. DIN EN60529	IP21	
RS232 interface	Yes	

SPECIFICATIONS

Model	SK-D3309-Pro	SK-R330-Pro
Power supply	110/220V, 50/60Hz	
Power	40W	
Motor type	DC motor	
Rocking motion	3D orbital	See-saw rocking
Tilt angle [o]	9o	9o
Max. load capacity (with platform) [kg]	5	10
Speed range [rpm]	10-70	
Speed display	LCD	
Timer	Yes	
Timer display	LCD	
Time setting range [min]	1-1199	
Operation type	Continuous/ timed operation	
Dimensions [D*W*H mm]	430*360*106	410*360*200
Weight [kg]	9	
Permissible ambient temperature [°C]	5-40	
Permissible relative humidity	80%	
Protection class acc. To DIN EN60529	IP21	