

memert (germany) UN 30



MODEL			UN30
Stainless steel interior	Volume	approx. l	32
	Width	Mm	400
	Height	Mm	320
	Depth (less 39 mm for fan)	Mm	250
	Stainless steel grids (standard equipment)	Number	1
	Max. number of grids/shelves	Number	3
	Max. loading per grid/shelf	Kg	20
	Max. loading of chamber	Kg	60
Textured stainless steel exterior	Width	Mm	585
	Height (size 450, 750, 1060 with castors)	Mm	704
	Depth (without door handle), door handle + 56 mm	Mm	434
Further data	Electrical load at 230 V, 50/60 Hz	approx. W	1600
	Electrical load at 115 V, 50/60 Hz	approx. W	1600
	Electrical load at 400 V and 3 x 230 V w/o neutral, 50/60 Hz	approx. W	—
	Working-temperature range	°C	at least 5 (UN/UNplus) at least 10 (UF/UFplus) above ambient temperature



			to +300
	Setting temperature range	°C	+20 to +300
	Setting accuracy	°C	up to 99.9: 0.1 / from 100: 0.5
Packing data	Net weight	approx. Kg	45
	Gross weight (packed in carton)	approx. Kg	61
	Width	approx. Kg	66
	Height	approx. Kg	89
	Depth	approx. kg	65

