

## Memmert UF 75 VOL/LTR 74



Model sizes/Description			75
<b>Stainless steel Interior</b>	Volume	approx. l	74
	Width	Mm	400
	Height	Mm	560
	Depth (less 39 mm for fan)	Mm	330
	Stainless steel grids (standard equipment)	Number	2
	Max. number of grids/shelves	Number	6
	Max. loading per grid/shelf	Kg	20
	Max. loading of chamber	Kg	120
<b>Textured stainless steel exterior</b>	Width	Mm	585
	Height (size 450, 750, 1060 with castors)	Mm	944
	Depth (without door handle), door handle + 56 mm	Mm	514
<b>Further data</b>	Electrical load at 230 V, 50/60 Hz	approx. W	2500
	Electrical load at 115 V,	approx. W	2200

	50/60 Hz		
	Electrical load at 400 V and 3 x 230 V w/o neutral, 50/60 Hz	approx. W	–
	Working-temperature range	°C	at least 5 (UN/UNplus) at least 10 (UF/UFplus) above ambient temperature to +300
	Setting temperature range	°C	+20 to +300
	Setting accuracy	°C	up to 99.9: 0.1 / from 100: 0.5
<b>Packing data</b>	Net weight	approx. Kg	66
	Gross weight (packed in carton)	approx. Kg	85
	Width	approx. Cm	73
	Height	approx. Cm	113
	Depth	approx. Cm	67

# DUTA MEDIKA

