

Memmert UF 750 VOL/LTR 749



MODEL		UF 750	
Stainless steel interior	Volume	approx. l	749
	Width	Mm	1040
	Height	Mm	1200
	Depth	Mm	600
	Stainless steel grids (standard equipment)	Number	2
	Max. number of grids/shelves	Number	14
	Max. loading per grid/shelf	Kg	30
	Max. loading of chamber	Kg	300
Textured stainless steel exterior	Width	Mm	1224
	Height	Mm	1726
	Depth (without door handle, depth of handle 2 x 56 mm)	Mm	784
Further data	Electrical load at 230 V, 50/60 Hz	approx. W	–
	Electrical load at 115 V, 50/60 Hz	approx. W	–
	Electrical load at 400 V and 3 x 230 V w/o	approx. W	7000

	neutral, 50/60 Hz		
	Working-temperature range	°C	at least 10 above ambient temperature to +300
	Setting temperature range	°C	+20 to +300
	Setting accuracy	°C	up to 99.9: 0.1 / from 100: 0.5
Packing data	Net weight	approx. Kg	260
	Gross weight in Triwall carton	approx. Kg	331
	Width	approx. Kg	133
	Height	approx. Kg	192
	Depth	approx. kg	105

DUTA MEDIKA



(0274) 7455898
081-327-234-498 / 089-627-021-444



info@dutamedika.com
www.jualperalatankeehatan.com



535A7543



081-327-234-498