

## IKA C-MAG HS4 IKAMAG Ceramic Magnetic Hotplate Stirrer, 3581001



### SPECIFICATIONS

<b>Number of stirring positions</b>	1
<b>Stirring quantity max. (H2O)</b>	5 l
<b>Motor rating input</b>	15 W
<b>Motor rating output</b>	1.5 W
<b>Speed display</b>	scale
<b>Speed range</b>	100 - 1500 rpm
<b>Heat output</b>	250 W
<b>Heating rate (1 l H2O in H15)</b>	2.5 K/min
<b>Heating temperature range</b>	50 - 500 °C
<b>Heat control</b>	LED
<b>Heat control accuracy</b>	10 ±K
<b>Speed control</b>	scale 0 - 6
<b>Fixed safety circuit</b>	550 °C
<b>Set-up plate material</b>	ceramic
<b>Set-up plate dimensions</b>	100 x 100 mm
<b>Dimensions (W x H x D)</b>	150 x 105 x 260 mm
<b>Weight</b>	3 kg
<b>Permissible ambient temperature</b>	5 - 40 °C
<b>Permissible relative humidity</b>	80%
<b>Protection class according to DIN EN 60529</b>	IP 21
<b>Voltage</b>	230 / 120 / 100 V

