

IKA Eurostar 40 Digital Overhead Stirre



MODEL	IKA Eurostar 40 Digital Overhead Stirre
Stirring quantity max. (H ₂ O)	25 l
Motor rating input	118 W
Motor rating output	84 W
Motor principle	Brushless DC
Speed display	7 segment LED
Speed range	0/30 - 2000 rpm
Reversible direction of rotation	no
Intermittent operation	no
Viscosity max.	30000 mPas
Output max. at stirring shaft	84 W
Permissible ON time	100 %
Torque max. at stirring shaft	40 Ncm
Speed control	stepless
Setting accuracy speed	1 ±rpm
deviation of speed measurement n > 300rpm	3 ±rpm
deviation of speed measurement n < 300rpm	1 ±%
Stirring element fastening	chuck
Temperature display	no
Chuck range min. diameter	0.5 mm
Chuck range max. diameter	10 mm



Hollow shaft, inner diameter	11 mm
Hollow shaft (push-through & when stopped)	yes
Fastening on stand	extension arm
Extension arm diameter	16 mm
Extension arm length	220 mm
Torque display	no
Nominal torque	0.4 Nm
Timer	no
housing material	alu-cast coating / thermoplastic polymer
clean room qualified	no
explosion proofed	no
Dimensions (W x H x D)	86 x 248 x 208 mm
Weight	4.4 kg
Permissible ambient temperature	5 - 40 °C
Permissible relative humidity	80 %
Protection class according to DIN EN 60529	IP 40
RS 232 interface	no
USB interface	no
Analog output	no
Voltage	230 / 115 / 100 V
Frequency	50/60 Hz
Power input	118 W

DUTA MEDIKA



(0274) 7455898
081-327-234-498 / 089-627-021-444



info@dutamedika.com
www.jualperalatankeehatan.com



535A7543



081-327-234-498