

IKA Eurostar 20 High Speed Digital Overhead Stirrer



MODEL	Eurostar 20 High Speed Digital
Stirring quantity max. (H ₂ O)	20 l
Motor rating input	176 W
Motor rating output	125 W
Motor principle	Brushless DC
Speed display	7 segment LED
Speed range	0/150 - 6000 rpm
Reversible direction of rotation	no
Intermittent operation	no
Viscosity max.	10000 mPas
Output max. at stirring shaft	125 W
Permissible ON time	100 %
Torque max. at stirring shaft	20 Ncm
Speed control	stepless
Setting accuracy speed	1 ±rpm
deviation of speed measurement n > 300rpm	3 ±rpm
deviation of speed measurement n < 300rpm	1 ±%
Stirring element fastening	special output shaft
Hollow shaft (push-through ; when stopped)	no
Fastening on stand	extension arm



Extension arm diameter	16 mm
Extension arm length	220 mm
Nominal torque	0.2 Nm
Timer	no
housing material	alu-cast coating / thermoplastic polymer
clean room qualified	no
explosion proofed	no
Dimensions (W x H x D)	86 x 325 x 208 mm
Weight	5.3 kg
Permissible ambient temperature	5 - 40 °C
Permissible relative humidity	80 %
Protection class according to DIN EN 60529	IP 40
RS 232 interface	no
USB interface	no
Analog output	no
Voltage	230 / 115 / 100 V
Frequency	50/60 Hz
Power input	176 W

DUTA MEDIKA



(0274) 7455898
081-327-234-498 / 089-627-021-444



info@dutamedika.com
www.jualperalatankeehatan.com



535A7543



081-327-234-498